

article#	90992198
article description	Distribution box plastic wall mounted KOMBI BV 63/5 32/5 16/5 4xSSD NH KT3 IP54
description long	thermoplastic combination IP54 consists of: 1x thermoplastic wall mounted distribution box model SÖLDEN IP54 520x297x165 0TE 1x thermoplastic wall mounted distribution box model SÖLDEN IP54 520x297x165 2x14TE mounted side by side on 2x Wall brackets stainless steel 1xKT3 cable sleeve on top (cable diam.: 14-54mm) / cable relief provided by the customer 1xM50 cable gland on top (cable diam.: 32-38mm PG42) grey 1xNH-fuse switch 00 100A 3p (fuses included) for external output 1xC EE-socket 63A 5p 400V IP67 fused with 1x Tytan D02 63A 3p 1xC EE-socket 32A 5p 400V fused with 1xMCB 32A 3p C 1xC EE-socket 16A 5p 400V fused with 1xMCB 16A 3p C 4xSK-sockets 16A 250V IP54 fused with 4xMCB's 16A 1p C 1xRCD 63A/4/0.03A (TYP A 63AT) over all 16+32A outlets pre-fused with 1XTytan D02 63A 3p Tytan MCB and RCD are Eaton ÖVE VDE branded Distributor connection terminal plate 3p (I1-L3) 35 - 120 mm² wired Distributor copper bars conductor terminal (N&PE) 16 - 120 mm² wired
GTIN (EAN)	9003399273384
country of origin	AT
customs number	85371098
net weight	21.500 kg
minimum order quantity	1

ETIM 9.0	EC000379
CEE socket outlet 16 A	1x16A5p400V
CEE socket outlet 32 A	1x32A5p400V
CEE socket outlet 63 A	1x63A5p400V
Number of socket outlets with protective contact CEE 7/3 (type F)	4
Protection	Overcurrent switch/D0-system
Earth leakage switch	Earth leakage switch with IFN 30 mA (standard)
Number of miniature circuit breakers	6
Material housing	Plastic
Power supply/connection possibility	1 cable (branch line)
Type of mains connection	Other
Handling	Wall mounting
Degree of protection (IP)	IP54
Colour	Grey
Height	520 mm
Width	444 mm
Depth	140 mm



<https://www.pcelectric.at/shop/en/?func=detail&artnr=90992198>